

Membrane diffuser tube; special diffuser, silicone

Applications

- for pressure diffusion with fine bubbles
- for oxygen input for nitrification in activation basins
- for permanent and intermittent ventilation systems
- for an oxygen input and circulation in fixed-bed and bioreactors
- for the thorough mixing of activation basins (municipal and industrial)
- as sand trap louvre ventilation
- for diffusing storage and receiving tanks
- for the renaturation of lakes and rivers

- for aquacultures and fish farming

Properties

- Operating range: normal operation 4-6, minimum 2, maximum 10 and purge operation 12Nm³/h (h * m_{aer.})
- optimized flow properties
- very good resistance to wastewater and municipal sewerage in accordance with the latest instructions DWA-M 115
- easily and quickly fitted
- conform to RoHS guideline

Temperature Range

- -40 °C to +90 °C

Design, material


wall: silicone 70 ± 5 Shore A

Delivery variants

- transparent (standard)
- other accessories on www.norres.com

Size	I.D.	Length	Ventilation Length	Weight	Order No.
mm	mm	mm	mm	kg/Pcs	
63	64,5	570	500	0,220	626-0570-2701
63	64,5	820	750	0,320	626-0820-2701
63	64,5	1070	1000	0,420	626-1070-2701

Accessoires



CONNECT 684



CONNECT 685



CLAMP 682



CONNECT 683



CONNECT 229



CONNECT 681